

ZS SERIES
DRILLING & TAPPING MACHINE
ZS系列钻攻两用机

标准附件

- 钻夹头
- 锥柄接套
- 锥柄接杆
- 下刀铁
- 扳手

Standard accessories

- Drill chuck
- Taper sleeve
- Arbor
- Drift
- Wrench

特殊附件

- 眼护罩
- 平口钳
- 攻丝夹头

Special accessories

- Safety guard
- Vice
- Tapping chuck



ZS4112D/ZS4116D

ZS4120D/ZS4125D

ZS系列钻攻两用机特点

- 选用名牌电器，性能稳定，经久耐用；
- 钻孔攻丝转换方便快捷；
- 独特的主轴设计及专用接杆，确保夹头连接更可靠。

ZS Drilling-Tapping machine Characters

- Using famous electrical equipment, stable featureand everlasting.
- Change easily between drilling and tapping.
- Special spindle design and arbor make sure chuck conn-ections.



手柄杆(整体钢件)
FEED HANDLE (STEEL MATERIAL)



皮带张紧机构
BELT ADJUST MECHANISM



LED工作灯
LED LIGHT



套筒导向装置
QUILL ORIENTATION MECHANISM

型号 Model		ZS4112D/ZS4116D	ZS4120D/ZS4125D
最大钻孔/攻丝直径 Max.Drilling/Tapping capacity	mm	D:12/T:M10/M8 D:16/T:M12/M10	D:20/T:M20/M16 D:25/T:M24/M20
立柱直径 Diameter of column	mm	70	85
主轴最大行程 Spindle travel	mm	100	125
主轴中心至立柱母线距离 Distance spindle axis to column generating line	mm	193	240
主轴端至工作台面最大距离 Max. Distance spindle nose to table	mm	315	367
主轴端至底座台面最大距离 Max. Distance spindle nose to base	mm	556	630
主轴锥度 Spindle taper		B16/MT2	MT2/MT3
主轴转速范围 Spindle speeds range	r/min	480~4100	290~2150
主轴转速级数 Spindle speeds series		5	5
工作台面尺寸 Dimension of work table surface	mm	200 X 230	280 X 300
底座尺寸 Dimension of base	mm	528 X 360	590 X 375
总高 Overall height	mm	1037	1127
电动机 Power of motor	W	750	750/1100
毛重/净重 G.W/N.W	kg	108/90	165/140
包装尺寸 Packing dimension	cm	77 X 42 X 95	82 X 48 X 102